



Sound Blok + 100 (3 in 1)

3mm thick; .08mm Plastic; Sound Absorbing Foam

- ✓ 100% vapor proof.
- ✓ Impact Isolation Class (IIC) Rating of 65.
- ✓ Sound Transmission Class (STC) Rating of 67.
- ✓ Superior sound control. Reduces both airborne noise and impact sound transmission through the floor.
- ✓ Reduces subfloor imperfections and muffles hollow sounds.
- ✓ FAST & EASY installation with overlap moisture sealing tape. No tools required.
- ✓ Suitable for use over concrete and wood subfloors.
- ✓ Suitable for use over radiant-heating systems.
- ✓ Mold and mildew resistant.
- ✓ Heat resistant, cold resistant, humidity resistant.
- ✓ High tensile and tear strengths.
- ✓ Structural stability prolongs the life of your floors.

Moisture Blok 100 (2 in 1)

3mm thick; .04mm Plastic; taped overlap edge

- ✓ 100% vapor proof.
- ✓ Reduces subfloor imperfections and muffles hollow sounds.
- ✓ FAST & EASY installation with overlap moisture sealing tape. No tools required.
- ✓ Suitable for use over concrete and wood subfloors.
- ✓ Suitable for use over radiant-heating systems.
- ✓ Mold and mildew resistant.
- ✓ Heat resistant, cold resistant, humidity resistant.
- ✓ Structural stability prolongs the life of your floors.